

# Contents

<b>1</b>	<b>Classes</b>	<b>2</b>
1.1	lattice – Lattice . . . . .	2
1.1.1	Lattice – lattice . . . . .	2
1.1.1.1	createElement – create element . . . . .	3
1.1.1.2	bilinearForm – bilinear form . . . . .	3
1.1.1.3	isCyclic – Check whether cyclic lattice or not . . . . .	3
1.1.1.4	isIdeal – Check whether ideal lattice or not . . . . .	3
1.1.2	LatticeElement – element of lattice . . . . .	4
1.1.2.1	getLattice – Find lattice belongs to . . . . .	5
1.1.3	LLL(function) – LLL reduction . . . . .	6

# Chapter 1

## Classes

### 1.1 lattice – Lattice

- Classes
  - **Lattice**
  - **LatticeElement**
- Functions
  - **LLL**

#### 1.1.1 Lattice – lattice

##### Initialize (Constructor)

```
Lattice( basis: RingSquareMatrix, quadraticForm: RingSquareMatrix)  
    → Lattice
```

Create Lattice object.

##### Attributes

**basis** : The basis of self lattice.

**quadraticForm** : The quadratic form corresponding the inner product.

## Methods

### 1.1.1.1 createElement – create element

`createElement(self, compo: list) → LatticeElement`

Create the element which has coefficients with given compo.

### 1.1.1.2 bilinearForm – bilinear form

`bilinearForm(self, v_1: Vector, v_2: Vector) → integer`

Return the inner product of  $v_1$  and  $v_2$  with `quadraticForm`.

### 1.1.1.3 isCyclic – Check whether cyclic lattice or not

`isCyclic(self) → bool`

Check whether self lattice is a cyclic lattice or not.

### 1.1.1.4 isIdeal – Check whether ideal lattice or not

`isIdeal(self) → bool`

Check whether self lattice is an ideal lattice or not.

### 1.1.2 LatticeElement – element of lattice

#### Initialize (Constructor)

```
LatticeElement( lattice: Lattice, compo: list, ) → LatticeElement
```

Create LatticeElement object.

Elements of lattices are represented as linear combinations of basis. The class inherits **Matrix**. Then, instances are regarded as  $n \times 1$  matrix whose coefficients consist of compo, where  $n$  is the dimension of lattice.

lattice is an instance of Lattice object. compo is coefficients list of basis.

#### Attributes

**lattice** : the lattice which includes **self**

## Methods

1.1.2.1 `getLattice` – Find lattice belongs to

`getLattice(self)` → **Lattice**

Obtain the Lattice object corresponding to `self`.

### 1.1.3 LLL(function) – LLL reduction

**LLL(M: RingSquareMatrix) → L: RingSquareMatrix, T: RingSquareMatrix**

Return LLL-reduced basis for the given basis M.

The output L is the LLL-reduced basis. T is the transportation matrix from the original basis to the LLL-reduced basis.

#### Examples

```
>>> M=mat.Matrix(3,3,[1,0,12,0,1,26,0,0,13]);
>>> lat.LLL(M);
([1, 0, 0]+[0, 1, 0]+[0, 0, 13], [1L, 0L, -12L]+[0L, 1L, -26L]+[0L, 0L, 1L])
```

# Bibliography