

Unifont

Paul Hardy

This manual describes Unifont, a bitmap-based font covering the Unicode Basic Multilingual Plane and beyond, along with Unifont's utility programs.

Copyright © 2008–2019 Paul Hardy

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, with no Front-Cover Texts and no Back-Cover Texts.

Table of Contents

1	Introduction	1
2	Tutorial	2
2.1	Unicode	2
2.2	Unifont Structure	2
2.3	Hex File Format	2
2.4	Using Graphical Tools	3
2.5	Using Hexdraw	6
2.6	Checking Coverage	7
2.7	Custom Builds	8
2.8	One Glyph per File	9
2.9	Viewing a Unifont File Interactively	9
2.10	Seeing the Big Picture (Literally!)	9
2.11	Combining Circles	10
2.12	Installing Fonts on GNU/Linux	11
2.13	Creating a Brand New Font	11
2.14	Updates to Unicode	12
3	Reference	13
3.1	bdfimplode	13
3.1.1	bdfimplode NAME	13
3.1.2	bdfimplode SYNOPSIS	13
3.1.3	bdfimplode DESCRIPTION	13
3.1.4	bdfimplode FILES	13
3.1.5	bdfimplode SEE ALSO	13
3.1.6	bdfimplode AUTHOR	13
3.1.7	bdfimplode LICENSE	13
3.1.8	bdfimplode BUGS	13
3.2	hex2bdf	13
3.2.1	hex2bdf NAME	13
3.2.2	hex2bdf SYNOPSIS	13
3.2.3	hex2bdf DESCRIPTION	14
3.2.4	hex2bdf OPTIONS	14
3.2.5	hex2bdf EXAMPLE	14
3.2.6	hex2bdf FILES	14
3.2.7	hex2bdf SEE ALSO	14
3.2.8	hex2bdf AUTHOR	14
3.2.9	hex2bdf LICENSE	14
3.2.10	hex2bdf BUGS	14
3.3	hex2sfd	15
3.3.1	hex2sfd NAME	15
3.3.2	hex2sfd SYNOPSIS	15

3.3.3	hex2sfd DESCRIPTION	15
3.3.4	hex2sfd FILES	15
3.3.5	hex2sfd SEE ALSO	15
3.3.6	hex2sfd AUTHOR	15
3.3.7	hex2sfd LICENSE	15
3.3.8	hex2sfd BUGS	15
3.4	hexbraille	15
3.4.1	hexbraille NAME	15
3.4.2	hexbraille SYNOPSIS	15
3.4.3	hexbraille DESCRIPTION	16
3.4.4	hexbraille FILES	16
3.4.5	hexbraille SEE ALSO	16
3.4.6	hexbraille AUTHOR	16
3.4.7	hexbraille LICENSE	16
3.4.8	hexbraille BUGS	16
3.5	hexdraw	16
3.5.1	hexdraw NAME	16
3.5.2	hexdraw SYNOPSIS	16
3.5.3	hexdraw DESCRIPTION	16
3.5.4	hexdraw FILES	16
3.5.5	hexdraw SEE ALSO	17
3.5.6	hexdraw AUTHOR	17
3.5.7	hexdraw LICENSE	17
3.5.8	hexdraw BUGS	17
3.6	hexkinya	17
3.6.1	hexkinya NAME	17
3.6.2	hexkinya SYNOPSIS	17
3.6.3	hexkinya DESCRIPTION	17
3.6.4	hexkinya FILES	17
3.6.5	hexkinya SEE ALSO	17
3.6.6	hexkinya AUTHOR	17
3.6.7	hexkinya LICENSE	18
3.6.8	hexkinya BUGS	18
3.7	hexmerge	18
3.7.1	hexmerge NAME	18
3.7.2	hexmerge SYNOPSIS	18
3.7.3	hexmerge DESCRIPTION	18
3.7.4	hexmerge FILES	18
3.7.5	hexmerge SEE ALSO	18
3.7.6	hexmerge AUTHOR	18
3.7.7	hexmerge LICENSE	18
3.7.8	hexmerge BUGS	18
3.8	johab2ucs2	19
3.8.1	johab2ucs2 NAME	19
3.8.2	johab2ucs2 SYNOPSIS	19
3.8.3	johab2ucs2 DESCRIPTION	19
3.8.4	johab2ucs2 FILES	19
3.8.5	johab2ucs2 SEE ALSO	19

3.8.6	johab2ucs2 AUTHOR.....	19
3.8.7	johab2ucs2 LICENSE.....	19
3.8.8	johab2ucs2 BUGS	19
3.9	unibdf2hex	19
3.9.1	unibdf2hex NAME	19
3.9.2	unibdf2hex SYNOPSIS	19
3.9.3	unibdf2hex DESCRIPTION	20
3.9.4	unibdf2hex FILES	20
3.9.5	unibdf2hex SEE ALSO	20
3.9.6	unibdf2hex AUTHOR	20
3.9.7	unibdf2hex LICENSE.....	20
3.9.8	unibdf2hex BUGS	20
3.10	unibmp2hex	20
3.10.1	unibmp2hex NAME	20
3.10.2	unibmp2hex SYNOPSIS.....	20
3.10.3	unibmp2hex DESCRIPTION	20
3.10.4	unibmp2hex OPTIONS.....	21
3.10.5	unibmp2hex EXAMPLE.....	21
3.10.6	unibmp2hex FILES.....	21
3.10.7	unibmp2hex SEE ALSO.....	21
3.10.8	unibmp2hex AUTHOR.....	21
3.10.9	unibmp2hex LICENSE	21
3.10.10	unibmp2hex BUGS.....	21
3.11	unibmpbump.....	22
3.11.1	unibmpbump NAME	22
3.11.2	unibmpbump SYNOPSIS.....	22
3.11.3	unibmpbump DESCRIPTION	22
3.11.4	unibmpbump OPTIONS.....	22
3.11.5	unibmpbump FILES.....	23
3.11.6	unibmpbump SEE ALSO.....	23
3.11.7	unibmpbump AUTHOR.....	23
3.11.8	unibmpbump LICENSE	23
3.11.9	unibmpbump BUGS.....	23
3.12	unicoverage	23
3.12.1	unicoverage NAME.....	23
3.12.2	unicoverage SYNOPSIS.....	23
3.12.3	unicoverage DESCRIPTION	23
3.12.4	unicoverage OPTIONS	23
3.12.5	unicoverage EXAMPLE	24
3.12.6	unicoverage FILES	24
3.12.7	unicoverage SEE ALSO.....	24
3.12.8	unicoverage AUTHOR.....	24
3.12.9	unicoverage LICENSE	24
3.12.10	unicoverage BUGS	24
3.13	unidup.....	24
3.13.1	unidup NAME	24
3.13.2	unidup SYNOPSIS	24
3.13.3	unidup DESCRIPTION	24

3.13.4	unidup FILES	24
3.13.5	unidup SEE ALSO	25
3.13.6	unidup AUTHOR	25
3.13.7	unidup LICENSE	25
3.13.8	unidup BUGS	25
3.14	unifont-viewer	25
3.14.1	unifont-viewer NAME	25
3.14.2	unifont-viewer SYNOPSIS	25
3.14.3	unifont-viewer DESCRIPTION	25
3.14.4	unifont-viewer FILES	25
3.14.5	unifont-viewer SEE ALSO	25
3.14.6	unifont-viewer AUTHOR	26
3.14.7	unifont-viewer LICENSE	26
3.14.8	unifont-viewer BUGS	26
3.15	unifont1per	26
3.15.1	unifont1per NAME	26
3.15.2	unifont1per SYNOPSIS	26
3.15.3	unifont1per DESCRIPTION	26
3.15.4	unifont1per OPTIONS	26
3.15.5	unifont1per FILES	26
3.15.6	unifont1per SEE ALSO	26
3.15.7	unifont1per AUTHOR	27
3.15.8	unifont1per LICENSE	27
3.15.9	unifont1per BUGS	27
3.16	unifontchojung	27
3.16.1	unifontchojung NAME	27
3.16.2	unifontchojung SYNOPSIS	27
3.16.3	unifontchojung DESCRIPTION	27
3.16.4	unifontchojung FILES	27
3.16.5	unifontchojung SEE ALSO	27
3.16.6	unifontchojung AUTHOR	27
3.16.7	unifontchojung LICENSE	28
3.16.8	unifontchojung BUGS	28
3.17	unifontksx	28
3.17.1	unifontksx NAME	28
3.17.2	unifontksx SYNOPSIS	28
3.17.3	unifontksx DESCRIPTION	28
3.17.4	unifontksx FILES	28
3.17.5	unifontksx SEE ALSO	28
3.17.6	unifontksx AUTHOR	28
3.17.7	unifontksx LICENSE	28
3.17.8	unifontksx BUGS	28
3.18	unifontpic	29
3.18.1	unifontpic NAME	29
3.18.2	unifontpic SYNOPSIS	29
3.18.3	unifontpic DESCRIPTION	29
3.18.4	unifontpic OPTIONS	29
3.18.5	unifontpic EXAMPLES	29

3.18.6	unifontpic FILES	29
3.18.7	unifontpic SEE ALSO	30
3.18.8	unifontpic AUTHOR	30
3.18.9	unifontpic LICENSE	30
3.18.10	unifontpic BUGS	30
3.19	unigencircles	30
3.19.1	unigencircles NAME	30
3.19.2	unigencircles SYNOPSIS	30
3.19.3	unigencircles DESCRIPTION	30
3.19.4	unigencircles EXAMPLE	30
3.19.5	unigencircles FILES	30
3.19.6	unigencircles SEE ALSO	31
3.19.7	unigencircles AUTHOR	31
3.19.8	unigencircles LICENSE	31
3.19.9	unigencircles BUGS	31
3.20	unigenwidth	31
3.20.1	unigenwidth NAME	31
3.20.2	unigenwidth SYNOPSIS	31
3.20.3	unigenwidth DESCRIPTION	31
3.20.4	unigenwidth EXAMPLE	31
3.20.5	unigenwidth FILES	31
3.20.6	unigenwidth SEE ALSO	32
3.20.7	unigenwidth AUTHOR	32
3.20.8	unigenwidth LICENSE	32
3.20.9	unigenwidth BUGS	32
3.21	unihex2bmp	32
3.21.1	unihex2bmp NAME	32
3.21.2	unihex2bmp SYNOPSIS	32
3.21.3	unihex2bmp DESCRIPTION	32
3.21.4	unihex2bmp OPTIONS	32
3.21.5	unihex2bmp EXAMPLE	33
3.21.6	unihex2bmp FILES	33
3.21.7	unihex2bmp SEE ALSO	33
3.21.8	unihex2bmp AUTHOR	33
3.21.9	unihex2bmp LICENSE	33
3.21.10	unihex2bmp BUGS	33
3.22	unihex2png	33
3.22.1	unihex2png NAME	33
3.22.2	unihex2png SYNOPSIS	33
3.22.3	unihex2png DESCRIPTION	33
3.22.4	unihex2png OPTIONS	34
3.22.5	unihex2png EXAMPLE	34
3.22.6	unihex2png FILES	34
3.22.7	unihex2png SEE ALSO	34
3.22.8	unihex2png AUTHOR	34
3.22.9	unihex2png LICENSE	34
3.22.10	unihex2png BUGS	35
3.23	unihexfill	35

3.23.1	unihexfill NAME	35
3.23.2	unihexfill SYNOPSIS	35
3.23.3	unihexfill DESCRIPTION	35
3.23.4	unihexfill OPTIONS	35
3.23.5	unihexfill FILES	35
3.23.6	unihexfill EXAMPLE	35
3.23.7	unihexfill SEE ALSO	35
3.23.8	unihexfill AUTHOR	36
3.23.9	unihexfill LICENSE	36
3.23.10	unihexfill BUGS	36
3.24	unihexgen	36
3.24.1	unihexgen NAME	36
3.24.2	unihexgen SYNOPSIS	36
3.24.3	unihexgen DESCRIPTION	36
3.24.4	unihexgen OPTIONS	36
3.24.5	unihexgen FILES	36
3.24.6	unihexgen EXAMPLE	36
3.24.7	unihexgen SEE ALSO	37
3.24.8	unihexgen AUTHOR	37
3.24.9	unihexgen LICENSE	37
3.24.10	unihexgen BUGS	37
3.25	unihexrotate	37
3.25.1	unihexrotate NAME	37
3.25.2	unihexrotate SYNOPSIS	37
3.25.3	unihexrotate DESCRIPTION	37
3.25.4	unihexrotate OPTIONS	38
3.25.5	unihexrotate EXAMPLES	38
3.25.6	unihexrotate FILES	38
3.25.7	unihexrotate SEE ALSO	38
3.25.8	unihexrotate AUTHOR	38
3.25.9	unihexrotate LICENSE	38
3.25.10	unihexrotate BUGS	38
3.26	unipagecount	38
3.26.1	unipagecount NAME	38
3.26.2	unipagecount SYNOPSIS	39
3.26.3	unipagecount DESCRIPTION	39
3.26.4	unipagecount OPTIONS	39
3.26.5	unipagecount FILES	39
3.26.6	unipagecount SEE ALSO	39
3.26.7	unipagecount AUTHOR	39
3.26.8	unipagecount LICENSE	39
3.26.9	unipagecount BUGS	39
3.27	unipng2hex	40
3.27.1	unipng2hex NAME	40
3.27.2	unipng2hex SYNOPSIS	40
3.27.3	unipng2hex DESCRIPTION	40
3.27.4	unipng2hex OPTIONS	40
3.27.5	unipng2hex EXAMPLE	40

3.27.6	unipng2hex FILES	40
3.27.7	unipng2hex SEE ALSO	40
3.27.8	unipng2hex AUTHOR	40
3.27.9	unipng2hex LICENSE	41
3.27.10	unipng2hex BUGS	41

1 Introduction

This document describes the process of using the GNU Unifont utilities to create a font. The steps described in the "Using Graphical Tools" section in the "Tutorial" chapter are more or less the steps that I (Paul Hardy) followed to add thousands of glyphs to GNU Unifont, except that I didn't have the luxury of just typing `make` to make a new font while adding those glyphs in the beginning.

I streamlined the font build process after I was done drawing the Unicode 5.1 glyphs.

If you have questions, please email unifoundry@unifoundry.com. You can check for the latest Unifont news at <http://savannah.gnu.org/projects/unifont> and <http://unifoundry.com>. You can also submit a bug report through the <http://savannah.gnu.org/projects/unifont> page.

DISCLAIMER: Donald Knuth warned in his Metafont book that if someone started designing type, they would never again be able to look at a page of text normally and just read its content. There is a point of no return beyond which a serious font designer begins looking at how individual letters in a font on a page are drawn, and how they might be improved. Be warned!

— Paul Hardy (unifoundry@unifoundry.com) 2008, 2013

2 Tutorial

This chapter provides a step-by-step tutorial on using the Unifont utility programs to modify a font in the GNU Unifont format.

2.1 Unicode

Unicode is an international standard to encode all the world's scripts with one universal scheme. Unicode is the default encoding for web pages and is gaining popularity in many other applications. To learn more about Unicode, look at code charts, and see the latest developments, check out

<http://unicode.org>

Unifont follows the Unicode encoding scheme. Unicode defines the numeric value of a character, but does not define one particular font. There can be (and are) many fonts that support a subset of Unicode characters.

In 1998, Roman Czyborra observed that there was still no font, free or commercial, with complete Unicode coverage. He envisioned a low-quality bitmapped font as an easy way to produce a font that covered much of the Unicode standard.

2.2 Unifont Structure

GNU Unifont is a bitmapped pixel font, which is also converted to an outline TrueType font. Roman Czyborra began this font in 1998 with a goal of having one glyph rendered for each visible character in the Unicode Basic Multilingual Plane (Plane 0, the first 65,536 characters). His original writing on this is at <http://czyborra.com/unifont/>.

(Note that the term "character" is used very loosely here for simplicity; the Unicode Standard has a stricter definition of what constitutes a character.)

The font is dual-width. Each character is 16 pixels tall, and either 8 or 16 pixels wide. The characters are stored in a unique .hex file format invented by Roman Czyborra as a convenient way of giving each character exactly a one line specification. Conversion between this .hex format and BDF font format is trivial.

Glyphs can actually be 8, 16, 24, or 32 pixels wide, but this extended capability should be considered experimental. Prior to the release of Unicode 10.0.0, hooks were put in place in some of the Unifont utilities to allow for the possibility of future fonts to represent complex glyphs such as Cuneiform. Unicode 10.0.0 created a need for quadruple-width glyphs (31 pixels wide, encoded as 32 pixels wide) for some historic Chinese ideographs assigned to the BMP; that currently is the only place glyphs other than single- or double-width are used. As a result, those Unifont utilities that support quadruple-width glyphs have updated descriptions in the reference section of this document.

2.3 Hex File Format

By convention, files containing the Unifont native font format have the extension ".hex". Their format is extremely simple, consisting of two fields separated with a colon (":") and ending with a newline.

The first field is the Unicode code point, in hexadecimal. For all Plane 0 code points, this is a four digit hexadecimal number. Hexadecimal digits are (in order) 0, 1, 2, 3, 4, 5, 6, 7, 8,

9, A, B, C, D, E, and F. The Unicode Standard uses a hexadecimal number to assign each character a location. These locations are called "code points" and their range is 0 through 10FFFF, inclusive.

The range 0000 through FFFF, inclusive, is called the Basic Multilingual Plane (BMP), or Plane 0. This plane contains glyphs for most of the world's modern writing scripts.

Unifont utilities support glyphs across the entire Unicode range. The current distribution includes glyphs for Unicode's Plane 0, Plane 1 (the Supplemental Multilingual Plane, or SMP), and others. Coverage of the SMP is only partial.

The first field in a `.hex` file should be either four digits long for the Basic Multilingual Plane, or six digits long for higher Unicode planes, following the convention of the Unicode Standard.

The second field is a string of hexadecimal digits. There are 32 digits for a character that is 8 pixels wide, and 64 digits for a character that is 16 pixels wide.

The good news is you don't have to worry about these long digit strings. Roman Czyborra wrote a utility, `hexdraw`, to convert `.hex` fonts to a form that can be edited with a plain text editor, then converted back into `.hex` format.

Paul Hardy wrote two utilities to do the same thing except with bitmapped graphics images for editing with a graphics editor: `unihex2bmp` converts a block of 256 characters into a graphics file, and `unibmp2hex` converts such a graphics file back into `.hex` format. These bitmaps display the 256 characters in a block arranged in a 16 by 16 character grid. The graphics editor must maintain the image as a monochrome (black and white) file, with one bit per pixel. After conversion from a `.bmp` file back to a `.hex` file, the next step is conversion to a BDF font file. A BDF file can only encode a pixel being on or off (i.e., black or white only with no intermediate shades of gray).

Andrew Miller later converted `unihex2bmp` and `unibmp2hex` to Perl, transforming them into `unihex2png` and `unipng2hex`, respectively. These programs convert Unifont `.hex` files to and from Portable Network Graphics files.

The `unihex2png`, `unipng2hex`, and `hexdraw` programs handle the full Unicode code point range of 0x000000 through 0x10FFFF. The `unihex2bmp` and `unibmp2hex` programs support the full 32-bit unsigned integer range of 0x00000000 through 0xFFFFFFFF, but have not been tested extensively beyond the Unicode upper limit of 0x10FFFF. The range of the C programs might be truncated in the future to only cover to 0x10FFFF, the limit of the Unicode code point space.

2.4 Using Graphical Tools

Let's look at an example. Suppose you want to modify the Coptic letters in the range U+2C80..U+2CFF ("U+" is Unicode shorthand). These letters are in the upper half of the block U+2C00..U+2CFF. The Unicode utilities in this package refer to this as "page" 2C. ("Page" is not a Unicode term — it is just a term unique to this package to refer to a block of 256 code points/characters).

The steps to follow will be:

1. Convert `.hex` version of the page 2C range as a 16 by 16 bitmapped grid.
2. Modify the bitmap in any graphics editor, being careful to re-save it as a Windows Bitmap (`.bmp`) or Wireless Bitmap file when finished.

3. Convert the modified bitmap back into a `.hex` font file.
4. Merge the results with the original `unifont.hex` file (or whatever its name might be).
5. Run `unidup` on the resulting file to guard against duplicate character definitions.
6. Create the new bitmapped version of the font.
7. Check the compiled font for duplicates.
8. If there are duplicates, remove them and go back to Step 5.
9. Create the new TrueType version or other versions of the font.

If the script has combining characters (such as accent glyphs), also add their code points to the proper `*combining.txt` file in the directory for the corresponding Unicode plane. That way, when the font is converted to TrueType those glyphs will have zero space. For a script with combining characters, all glyphs that can appear with combining characters must have the same width so that the combining characters will be properly positioned.

Step 1: Convert the `.hex` range into a bitmap grid. Assuming our font file is named `unifont.hex`, type

```
unihex2bmp -p2C < unifont.hex > uni2C.bmp
```

Step 2: Modify `uni2C.bmp` with your favorite graphics editor. Note that whatever graphics editor you use must preserve the file as a black and white bitmap (monochrome), with one bit per pixel. During editing, you can draw guidelines outside the actual 16x16 font pixel area; they will be ignored when converting back into `.hex` format. You can also erase the grid borders between code points on purpose or by accident, and it will have no effect on the generated `.hex` file. Just don't erase the code point numbers on the outer edges of the grid. The conversion from `.bmp` back to `.hex` only looks at the "U+0000" in the upper left-hand corner of the bitmap graphic and other code point numbers, and at each code point's 16x16 pixel area inside its 32x32 pixel grid area. Every other artifact in the final graphics file outside these areas is ignored.

If a new version of Unicode adds glyphs to a page that were previously unassigned, be sure to remove the newly-assigned code points from the `unassigned.hex` file because the code point is no longer unassigned.

Step 3: Convert the edited `.bmp` file back into `.hex` format:

```
unibmp2hex < uni2C.bmp > uni2C.hex
```

Note that the conversion from a bitmap image to a `.hex` file can't distinguish between a legitimate single- or double-width space character and a code point that does not have an assigned value. Therefore, space glyphs are separately contained in the `spaces.hex` file.

Step 4: Merge the results with the original `unifont.hex` file. This requires several sub-steps:

- Edit the original `unifont.hex` file and delete the lines that begin with "2C".
- Insert the `uni2C.hex` file into `unifont.hex`, either with a text editor such as `emacs` or `vi`, or with a GNU/Linux command such as:

```
sort uni2C.hex unifont.hex > new-unifont.hex
```

This second option (using `sort`) is preferred, because `unidup` (in Step 5) might miss duplicate code points if your final result isn't in proper order.

Step 5: Make sure there are no duplicates with `unidup`:

```
unidup < unifont.hex
```

or

```
unidup < new-unifont.hex
```

depending on the name of your final font file. If there is no output, your modified font contains no duplicates.

This editing is best done on an input .hex file, such as `unifont-base.hex`.

Step 6: Create the new bitmapped version of the font. In the `font/` directory, type

```
make hex
```

Step 7: Check the compiled font for duplicates. Change to the `font/compiled/` directory and run

```
unidup < mynewfontfile.hex
```

for whatever font file you created.

Step 8: If there are duplicates, remove them in the `font/` directory and go back to Step 5.

Step 9: Create the new TrueType version of the font and all other bitmapped versions. From the `font/` directory, type

```
make distclean && make
```

Then be prepared to wait a long time unless you are using a computer with plenty of RAM and CPU horsepower. Your computer should have at least 256 Megabytes of virtual memory (RAM), and at least 250 Megabytes of free disk space.

To only create a BDF font, in the `font/` directory just type

```
make bdf
```

To only create a BDF and PCF font, in the `font/` directory type

```
make pcf
```

Creating a BDF font is the first step in creating a PCF font (not counting generating the compiled master ".hex" input file). BDF fonts can be created just with the tools in this package. PCF fonts are created by running `bdftopcf` on the BDF font. TrueType fonts require FontForge.

The Unifont package also includes two programs for working with Portable Network Graphics (PNG) files instead of BMP files. These utilities are `unihex2png` and `unipng2hex`. They work in a similar manner to the corresponding programs `unihex2bmp` and `unibmp2hex`, respectively.

To use `unihex2png` instead of `unihex2bmp`, continuing the example of the Coptic script in the U+2Cxx range, type:

```
unihex2png -p 2C -i unifont.hex -o uni2C.png
```

Note that with `unihex2bmp` specifying input and output files is optional, while with `unihex2png` at least the PNG filename must be specified explicitly. More specifically, `unihex2png` will read a .hex file format input from STDIN if no "-i" argument is specified, but the name of the binary PNG file must always be specified with the "-o" option.

Then edit the resulting PNG file to your heart's content. When done, convert the file back into a `unifont.hex` format file. In this example, type:

```
unipng2hex -i uni2C.png -o uni2C.hex
```

Similar to `unihex2png`, the binary PNG file must be specified with "-i" but the .hex format file will be written to STDOUT if the "-o" option is omitted.

Finally, merge your changes in with your main .hex font file as described previously in this section.

2.5 Using Hexdraw

Roman Czyborra's original utility to edit glyphs is the `hexdraw` Perl script. Using the same script as in the previous chapter, Coptic, here are the steps for modifying `unifont.hex` using `hexdraw`.

First, realize that Unifont has tens of thousands of glyphs (characters, using the term character loosely). In this example, out of the tens of thousands of glyphs, we want to modify the range U+2C80..U+2CFF (only 128 glyphs).

The range U+2C80..U+2CFF could be extracted from `unifont.hex` by using the `egrep` utility to look for lines beginning with "2C8" through "2CF", or that range could be isolated by copying `unifont.hex` into another file, and deleting all lines except the desired range.

The following steps will probably minimize typographical errors, but they aren't the only way.

1. "Grep" the desired block of 256 glyphs (using the `grep` utility) and convert this into a text representation for editing.
2. Edit the block with a text editor, such as `emacs` or `vi`.
3. Convert the edited text file back into .hex format.
4. Delete the edited block range from the original font file.
5. Merge the two .hex files into one file.
6. Check for duplicates with `unidup`.
7. Generate new fonts as described in the "Using Graphical Tools" section above.

Step 1: Extract the desired block with `grep`:

```
grep "^2C" unifont.hex | hexdraw > uni2C.txt
```

Step 2: Edit `uni2C.txt` with a text editor.

Step 3: Convert the text file back into .hex format:

```
hexdraw < uni2C.txt > uni2C.hex
```

Step 4: Delete the lines in the original `unifont.hex` file that begin with "2C".

Step 5: Merge the two files:

```
sort unifont.hex uni2C.hex > new-unifont.hex
```

or use Roman's `hexmerge` utility:

```
hexmerge unifont.hex uni2C.hex > new-unifont.hex
```

Step 6: Check for duplicates:

```
unidup < new-unifont.hex
```

Of course, remove any reported duplicates.

Step 7: Build the font as in the "Using Graphical Tools" section above. This can be as simple as typing

```
make
```

in the `font/` directory.

I (Paul Hardy) had only used `hexdraw` in the very beginning of my work on Unifont. Once I got my graphics programs working, I ignored it for months. Then I wanted to go through all of the Yi Syllables and Yi Radicals — over 1000 glyphs — to fine-tune their horizontal alignment after I drew them. `hexdraw` turned out to be the perfect tool for this. By printing hyphens ("-") as place holders where a pixel is off, it allowed me to verify space to the left and right of each character. I later used `hexdraw` for similar fine-tuning of spacing on Hangul and other glyphs. It is ideal for the task.

2.6 Checking Coverage

There should never be duplicates in a `.hex` file. If there are, remove them before the `.hex` font is turned into a BDF or other font file. The recommendations above include making liberal use of `unidup` to avoid such a situation.

The `unipagecount` program will print a hexadecimal number of code points that have coverage within each 256 code point block. The hexadecimal number will therefore range from 0 (no coverage) to 100 (= 256 decimal; full coverage). If a number is ever more than 100 hexadecimal, there's an extra character (glyph) for that page.

To further look at the coverage within just one 256 code point page (using page 2C, containing Coptic, as our example) use

```
unipagecount -p2C < unifont.hex
```

Note that the "page number" can use upper- or lower-case letters: `-p2C` or `-p2c` will both work. That will print a 16 x 16 grid of U+2C00..U+2CFF. Of course, without placeholder glyphs for the unassigned code points from `unassigned.hex` in the U+2C00..U+2CFF range, `unipagecount` can give a lower number than the true coverage.

Using the `-l` flag with `unipagecount` will produce an HTML table with links to corresponding graphics images. You can get an idea of how this works in the `font/compiled/` directory after running `make`; the `index.html` file in that directory will have a table with links to the 256 glyph maps in the `font/compiled/bmp/` subdirectory.

With `unipagecount`, the background color of the cells will range from red (for 0% complete in that 256 code point block) to orange (a little coverage) to yellow (more coverage) to green (complete coverage). If a cell looks light red or pink, the corresponding code page probably has duplicate characters. Verify that with

```
sort unifont.hex | unidup
```

(substituting the name of your `.hex` file for `unifont.hex`).

To see the coverage of each Unicode script, copy the file `font/coverage.dat` into the same directory as the `unifont.hex` file you're examining. Then run

```
unicoverage < unifont.hex > coverage.out
```

This will give you all the scripts within the Unicode Basic Multilingual Plane, in order, with a percentage (0.0% through 100.0%) of each script's coverage. Note that to get the true coverage of assigned code points, you'll have to merge `unassigned.hex` with the rest of `unifont.hex` if not done by default in your setup.

Using the `.hex` files in `font/plane00/`, you can create a font with all available glyphs with

```
sort font/plane00/*.hex >unifont-whole.hex
```

and run `unicoverage` using the resulting `unifont-whole.hex` file.

2.7 Custom Builds

The font can be built from within the `font/` directory by simply typing

```
make
```

From the top-level directory (one level above the `font/` directory), typing

```
make BUILDFONT=1
```

will also build the font. The font is not built by default by typing `make` from the top-level directory, because a pre-built version already exists in the `font/precompiled/` directory. Font files are architecture-independent, so the only reason to build the font is if you modify its composition.

By default, source glyphs are read from the `font/plane00/` directory. Glyphs for unassigned code points are built into the font by default, but glyphs for Private Use Area code points are not built into the font.

All of the `.hex` file names can be replaced selectively on the `make` command line to override their default values. Their locations are relative to the `font/` directory. The list of component hex file variables is:

<code>UNIFONTBASE</code>	The bulk of Unifont scripts
<code>CJK</code>	Most of the CJK Ideographs
<code>CUSTOM00</code>	Hand-drawn quadruple-length Plane 0 glyphs
<code>HANGUL</code>	Hangul Syllables block
<code>SPACES</code>	Space glyphs, single- and double-width
<code>UNASSIGNED</code>	Glyphs for unassigned code points
<code>PUA</code>	Glyphs for the Private Use Area

So, for example, to build a font that includes four-digit hexadecimal code point glyphs (as white digits on a black background) for the Private Use Area, type

```
make PUA="plane00/pua.hex"
```

because those glyphs reside in the `font/plane00/pua.hex` file.

To build a font that includes your own special PUA glyphs, type

```
make PUA="my-cool-PUA.hex"
```

or whatever the name of your PUA glyph `.hex` file is named.

To create a build that includes the supplied PUA glyphs but not the unassigned code point glyphs, type

```
make PUA="plane00/pua.hex" UNASSIGNED=""
```

If you create a custom font build of your own in one gigantic file, you can build with just this file by declaring all the ordinary files to be null:

```
make UNIFONTBASE="mycustomfont.hex" \
```

```
CJK="" HANGUL="" UNASSIGNED="" PUA=""
```

Note that this command did not include an override for the glyphs for spaces contained in the `font/plane00/spaces.hex` file; that is, the variable `SPACES` was not redefined on the command line. You could also pass the argument `SPACES=""`, but just be aware that those spaces glyphs are in a separate file for a reason. When graphical (".bmp") glyph files are converted back into hex string (".hex") format, the `unibmp2hex` utility doesn't know if a blank glyph area is a space glyph or not, so it doesn't encode anything. The `font/plane00/spaces.hex` file contains glyphs that are strings of 0s, with length depending on whether the space is nominally a single- or double-width space. (Unifont does not distinguish between finer spacing used in traditional typesetting, such as a thin space, en space, em space, or quad space; all spaces are either 8 pixels wide or 16 pixels wide.)

2.8 One Glyph per File

The `unifont1per` program will read a Unifont ".hex" file from standard input and create bitmap output files, one file per Unicode code point in the ".hex" file. This can be useful if you want to include single glyphs as graphic objects for illustration in a document or web page. Output files have names of the form "U+<codepoint>.bmp", where "<codepoint>" is the Unicode code point of the glyph.

Note that if you feed `unifont1per` a huge file of glyph hexadecimal strings, you will get a directory loaded with individual ".bmp" files, so use your judgment!

2.9 Viewing a Unifont File Interactively

The `unifont-viewer` Perl script uses the `wxWidgets` Perl library to present a dynamic graphical representation of a Unifont hex file. This is a convenient way to scan quickly through a complete Unifont hex file. It is ideal for scanning through a Unifont hex source file after you have made changes.

Use `unifont-viewer` to open any Unifont hex file, whether in the Basic Multilingual Plane up to the maximum Unicode code point of U+10FFFF. The font is displayed graphically in sections of 16-by-16 glyph grids (256 glyphs—a "page" in Unifont lingo). The page numbers (the upper portion of the hexadecimal code point range) appear in a list along the left-hand side. Only page ranges that are present in the Unifont hex file are listed.

When `unifont-viewer` loads a hex file, it begins by displaying the first "page" range in that file.

2.10 Seeing the Big Picture (Literally!)

The GNU Unifont 6.3 release introduced a new program, `unifontpic`. This produces a chart of all the Basic Multilingual Plane glyphs in Unifont. By default the chart is arranged as a 256-by-256 glyph table. Specifying the `-l` option produces a chart that is 16 glyphs wide by 4,096 glyphs long. See `unifontpic(1)` for more information.

The "long" version, created with `unifontpic -l`, only produces 16 glyphs per row. This is more useful for scrolling through on a computer screen.

GIMP, the GNU Image Manipulation Program, will properly display the resulting long .bmp file (at least under GNOME), but not all graphics utilities can. The output file is over 65,536 pixel rows tall, which causes problems with some graphics programs.

To generate a chart with all your glyphs in one giant `unifont.hex` file, type the command

```
unifontpic < unifont.hex > unifont.bmp
```

The output is a monochrome Bitmap Graphics Format (.bmp) file. If you prefer PNG files, use your favorite graphics program or conversion program to convert the BMP file to a PNG file.

This utility is especially useful if you're customizing the font, for example if adding your own Private Use Area glyphs.

Single-width and double-width glyphs are reproduced in this bitmap file at the correct aspect ratio. Triple-width and quadruple-width glyphs will be compressed 50% in the horizontal dimension to fit within a 16-by-16 pixel glyph cell.

The default 256-by-256 code point chart will render satisfactorily on a sheet of paper approximately 3 feet by 3 feet (1 meter by 1 meter) at 120 dots per inch. Thus the square format is suitable for printing.

2.11 Combining Circles

The earliest versions of Unifont (before the 5.1 release) used glyphs that showed dashed circles for combining characters. This is how the glyphs appear in The Unicode Standard code charts. In version 5.1, Paul Hardy was able to get combining characters to appear superimposed correctly in the TrueType version of the font. (There are no plans to try to get combining characters to work in a BDF or PCF version owing to the limitations of those bitmapped font formats.)

With combining characters working in the TrueType font, Paul Hardy created variations of Unifont with and without combining circles, the idea being that the version without combining circles would be used to create the TrueType font. The variation with combining circles was kept for reference.

Unifont Version 6.2 simplified the build to produce only one font variation, without combining circles.

Unifont Version 6.3 introduced a new utility, `unigencircles`, to superimpose combining circles over glyphs with code points in a `combining.txt` file.

The latest Unifont release contains a parallel set of font files named `unifont_sample.*`. These "Unifont Sample" font files contain glyphs with combining circles where appropriate. The "Unifont Sample" font is therefore not intended for general-purpose writing, but only for illustrating each individual glyph as represented in The Unicode Standard.

To run `unigencircles`, start with the file `font/ttfsrc/combining.txt` and type a command of this form:

```
unigencircles combining.txt < unifont.hex > unifont-circles.hex
```

where `unifont.hex` is a single file containing all the glyphs you wish to render. You could create such a file from the `font/` directory with the command

```
sort plane00/*.hex >unifont.hex
```

Because the output is another .hex file, you can use all Unifont utilities with this resulting file just as you would with the .hex files in `font/plane00/`.

If you want to build a font from this generated `unifont.hex` file, you could type

```
make UNIFONTBASE="unifont-circles.hex" CJK="" HANGUL="" \
    UNASSIGNED="" PUA=""
```

as discussed above. In this case, if you included `font/plane00/spaces.hex` in the `unifont.hex` input file, you should also set `SPACES=""` on the command line so that you only read in your final custom `unifont-circles.hex` file.

2.12 Installing Fonts on GNU/Linux

The original standard font format of Unifont was a BDF font. The newer PCF font format loads much faster when a program begins, and so is preferable for installations using the X Window System and similar environments.

Compress PCF fonts using

```
gzip -9 fontname.pcf
```

Copy the resulting `fontname.pcf.gz` file to `/usr/share/fonts/X11/misc/` or place in a local font directory if your windowing software supports that (for example, `~/.fonts/`).

Copy TrueType fonts to `/usr/share/fonts/truetype/` uncompressed or place in your local font directory. Note: on some versions of Unix, such as Solaris, the name of the TrueType directory might be `TrueType` and might be under `/usr/share/fonts/X11/` — examine the system fonts directories, then modify the font `make install` rule accordingly.

On most flavors of GNU/Linux with the latest `xset` utility (including the latest Debian and Red Hat releases), the following command should allow you to start using the font immediately:

```
xset fp rehash
```

The safest way to make sure the system knows about the new fonts will be to restart the X Window System or even reboot.

2.13 Creating a Brand New Font

The original tools will only produce glyphs that are 16 pixels tall, and either 8 or 16 pixels wide. The utilities `unihex2png`, `unipng2hex`, `hexdraw`, and `hex2bdf` now also support glyph heights of 24 and 32 pixels, and glyph widths of 8, 16, 24, and 32 pixels, but this is not fully tested. PNG glyphs that are 32 pixels wide are only supported if the glyphs are also 32 pixels tall. These dimensions are available for experimental use. See the respective sections for each of these programs in the Reference chapter of this document, or their respective man pages.

To create a brand new font (or even to add a new script to Unifont in the future), plan out the basic dimensions of the characters:

- How far above the lowest pixel will the baseline appear (in other words, how many rows are necessary for descenders such as in the glyphs for ‘g’, ‘q’, and ‘y’)?
- How many pixels must be empty on top and bottom for accents (in other words, what will the height of capital letters be)?
- Must glyphs be centered, left-aligned, or right-aligned?

- For a Latin font, what will the "x-height" be (the height of a lower-case "x" and related letters, such as "n" and "r")?

Consistent capital heights, x-heights, descender depths, and centering will produce a better looking font. Look over the entire script and plan out a template grid that is consistent for the entire script. Then use that template for each glyph you draw for the script.

Unifont characters for the most part leave the left-most or right-most column of pixels blank if possible (consistent within each script) for left-to-right scripts. Centering is done around the fourth pixel (if a glyph is eight pixels wide) or around the eighth pixel (if a glyph is 16 pixels wide).

Experimenting and (above all) having fun with these utilities is the best way to learn.

2.14 Updates to Unicode

If a currently unassigned code point is assigned to a character in the future, the font can be updated as follows:

1. Delete the code point's entry from `font/plane00/unassigned.hex`, as that code point will no longer be unassigned.
2. Determine which existing `.hex` file should contain the newly defined character (examine the files to see which one contains other glyphs in the script).
 - `unifont-base.hex` contains most scripts
 - `wqy.hex` contains most CJK ideographs; its name pays homage to the Wen Quan Yi font, the source of almost all of its glyphs
 - `hangul-syllables.hex` contains the Hangul Syllables block (U+AC00..U+D7A3); this should never have new code points added as it covers the fixed range of the Unicode Hangul Syllables block
 - `spaces.hex` contains the list of single- and double-width spaces

If in doubt (for example, if a new script is added to Unicode and you're not sure which `.hex` file to augment), add the new glyphs to `unifont-base.hex`.

3. Update the appropriate `.hex` file.
4. Consider if `font/coverage.dat` has to be updated. Follow its existing format to insert a new script, being sure to change any previously unassigned ranges before or after the newly added script.
5. Make a new `.hex` version of the font, and verify that you didn't introduce any duplicates.
6. Run `unipagecount` and/or `unicoverage` as described previously to verify that you have not mistakenly deleted any existing characters.

Enjoy!

3 Reference

3.1 bdfimplode

3.1.1 bdfimplode NAME

bdfimplode – Convert a BDF font into GNU Unifont .hex format

3.1.2 bdfimplode SYNOPSIS

bdfimplode < *input-font.bdf* > *output-font.hex*

3.1.3 bdfimplode DESCRIPTION

bdfimplode reads a BDF font from STDIN and writes GNU Unifont .hex conversion of the font to STDOUT.

3.1.4 bdfimplode FILES

*.bdf font files

3.1.5 bdfimplode SEE ALSO

hex2bdf(1), **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **jobab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigenircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.1.6 bdfimplode AUTHOR

bdfimplode was written by Roman Czyborra.

3.1.7 bdfimplode LICENSE

bdfimplode is Copyright © 1998 Roman Czyborra.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.1.8 bdfimplode BUGS

bdfimplode was written to read a BDF file created by the **hex2bdf** script. It will not properly handle other BDF files with differing bounding boxes.

3.2 hex2bdf

3.2.1 hex2bdf NAME

hex2bdf – Convert a GNU Unifont .hex file into a BDF font

3.2.2 hex2bdf SYNOPSIS

hex2bdf [*options*] < *input-font.hex* > *output-font.bdf*

3.2.3 hex2bdf DESCRIPTION

hex2bdf reads a sorted GNU Unifont .hex file (sorted with the Unix **sort** utility) from STDIN and writes a BDF version of the font to STDOUT.

3.2.4 hex2bdf OPTIONS

- f "font-name"**
Specify the target font name. If omitted, the default font name "Unifont" is assigned.
- v "font-version"**
Specify the target font version. If omitted, the default version "1.0" is assigned.
- c "font-copyright"**
Specify the target font copyright information. The default is the null string.

- r *pixel-rows*** Specify how many pixel rows tall a glyph is. The default is the traditional Unifont 16 rows of pixels. This is an addition to support **uni-hex2png(1)** and **unipng2hex(1)**, which allow designing glyphs that are 16, 24, or 32 pixel rows tall.

3.2.5 hex2bdf EXAMPLE

Sample usage:

```
hex2bdf -f "Unifont" -c "(C) 2013..." unifont.hex > unifont.bdf
```

3.2.6 hex2bdf FILES

*.hex GNU Unifont font files

3.2.7 hex2bdf SEE ALSO

bdfimplode(1), **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigenircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.2.8 hex2bdf AUTHOR

hex2bdf was written by Roman Czyborra.

3.2.9 hex2bdf LICENSE

hex2bdf is Copyright © 1998 Roman Czyborra.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.2.10 hex2bdf BUGS

No known bugs exist. Support for glyph heights other than 16 pixels is brand new and has not been extensively tested.

3.3 hex2sfd

3.3.1 hex2sfd NAME

hex2sfd – Convert a GNU Unifont .hex file into a FontForge .sfd format

3.3.2 hex2sfd SYNOPSIS

hex2sfd < *input-font.hex* > *output-font.sfd*

3.3.3 hex2sfd DESCRIPTION

hex2sfd reads a GNU Unifont .hex file from STDIN and writes an outline font representation in FontForge Spline Font Database (.sfd) format. The resulting .sfd file can then be converted by FontForge into a TrueType .ttf font.

3.3.4 hex2sfd FILES

GNU Unifont .hex font files for input, FontForge .sfd font files for output

3.3.5 hex2sfd SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigencircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.3.6 hex2sfd AUTHOR

hex2sfd was written by Luis Alejandro Gonzalez Miranda in 2005, with modifications by Paul Hardy in 2008.

3.3.7 hex2sfd LICENSE

hex2sfd is Copyright © 2005 Luis Alejandro Gonzalez Miranda, © 2008 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.3.8 hex2sfd BUGS

No known bugs exist.

3.4 hexbraille

3.4.1 hexbraille NAME

hexbraille – Algorithmically generate the Unicode Braille range (U+28xx)

3.4.2 hexbraille SYNOPSIS

hexbraille > *output-font.hex*

3.4.3 hexbraille DESCRIPTION

hexbraille generates a GNU Unifont .hex format file (written on stdout) containing the Braille dot patterns in the Unicode range U+2800..U+28FF.

3.4.4 hexbraille FILES

braille.hex output font files

3.4.5 hexbraille SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigencircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.4.6 hexbraille AUTHOR

hexbraille was written by Roman Czyborra, who named this script "braille.pl". In 2003, Roman incorporated a bug fix from Dominique at unruh.de.

3.4.7 hexbraille LICENSE

hexbraille is Copyright © 1998 Roman Czyborra.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.4.8 hexbraille BUGS

No known bugs exist.

3.5 hexdraw

3.5.1 hexdraw NAME

hexdraw – Convert a GNU Unifont .hex file to and from an ASCII text file

3.5.2 hexdraw SYNOPSIS

hexdraw < *input-font.hex* > *output-font.txt*

hexdraw < *input-font.txt* > *output-font.hex*

3.5.3 hexdraw DESCRIPTION

hexdraw reads a sorted GNU Unifont .hex file from STDIN and writes a two dimensional ASCII art rendering for each glyph to STDOUT. The output file can be edited with any text editor, then converted back into a .hex file. Unifont ASCII hexadecimal glyphs are 16 pixels high and can be 8, 16, 24, or 32 pixels wide.

3.5.4 hexdraw FILES

*.hex GNU Unifont font files

3.5.5 hexdraw SEE ALSO

`bdfimplode(1)`, `hex2bdf(1)`, `hex2sfd(1)`, `hexbraille(1)`, `hexkinya(1)`, `hexmerge(1)`, `johab2ucs2(1)`, `unibdf2hex(1)`, `unibmp2hex(1)`, `unibmpbump(1)`, `unicoverage(1)`, `unidup(1)`, `unifont(5)`, `unifont-viewer(1)`, `unifont1per(1)`, `unifontchojung(1)`, `unifontksx(1)`, `unifontpic(1)`, `unigencircles(1)`, `unigenwidth(1)`, `unihex2bmp(1)`, `unihex2png(1)`, `unihexfill(1)`, `unihexgen(1)`, `unihexrotate(1)`, `unipagecount(1)`, `unipng2hex(1)`

3.5.6 hexdraw AUTHOR

`hexdraw` was written by Roman Czyborra.

3.5.7 hexdraw LICENSE

`hexdraw` is Copyright © 1998 Roman Czyborra.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.5.8 hexdraw BUGS

No known bugs exist.

3.6 hexkinya

3.6.1 hexkinya NAME

`hexkinya` – Create the Private Use Area Kinya syllables

3.6.2 hexkinya SYNOPSIS

```
hexkinya > plane15.hex
```

3.6.3 hexkinya DESCRIPTION

`hexkinya` contains pre-defined initial, middle, and final Kinya alphabet glyphs to form syllables. The output is the Kinya Syllables Private Use Area block of the ConScript Unicode Registry (CSUR). The output range is U+0F0000 through U+0FDE6F, inclusive.

Note that Plane 15 also contains Pikto glyphs, which follow after Kinya.

3.6.4 hexkinya FILES

None.

3.6.5 hexkinya SEE ALSO

`bdfimplode(1)`, `hex2bdf(1)`, `hex2sfd(1)`, `hexbraille(1)`, `hexdraw(1)`, `hexmerge(1)`, `johab2ucs2(1)`, `unibdf2hex(1)`, `unibmp2hex(1)`, `unibmpbump(1)`, `unicoverage(1)`, `unidup(1)`, `unifont(5)`, `unifont-viewer(1)`, `unifont1per(1)`, `unifontchojung(1)`, `unifontksx(1)`, `unifontpic(1)`, `unigencircles(1)`, `unigenwidth(1)`, `unihex2bmp(1)`, `unihex2png(1)`, `unihexfill(1)`, `unihexgen(1)`, `unihexrotate(1)`, `unipagecount(1)`, `unipng2hex(1)`

3.6.6 hexkinya AUTHOR

`hexkinya` was written by Andrew Miller.

3.6.7 hexkinya LICENSE

hexkinya is Copyright © 2014 by Andrew Miller.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.6.8 hexkinya BUGS

No known bugs exist.

3.7 hexmerge

3.7.1 hexmerge NAME

hexmerge – Merge two or more GNU Unifont .hex font files into one

3.7.2 hexmerge SYNOPSIS

hexmerge *input-font1.hex input-font2.hex > output-font.hex*

3.7.3 hexmerge DESCRIPTION

hexmerge reads two or more GNU Unifont .hex files, sorts them, and writes the combined font to stdout.

3.7.4 hexmerge FILES

*.hex GNU Unifont font files

3.7.5 hexmerge SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexkinya(1)**, **hexdraw(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigenircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.7.6 hexmerge AUTHOR

hexmerge was written by Roman Czyborra.

3.7.7 hexmerge LICENSE

hexmerge is Copyright © 1998 Roman Czyborra.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.7.8 hexmerge BUGS

No known bugs exist.

3.8 johab2ucs2

3.8.1 johab2ucs2 NAME

`johab2ucs2` – Convert a Johab BDF font into GNU Unifont Hangul Syllables

3.8.2 johab2ucs2 SYNOPSIS

`johab2ucs2` < *input-font.bdf* > *output-font.hex*

3.8.3 johab2ucs2 DESCRIPTION

`johab2ucs2` reads a Johab encoded BDF font (as used in Hanterm) from STDIN and writes a GNU Unifont `.hex` file containing the Unicode Hangul Syllables to STDOUT.

3.8.4 johab2ucs2 FILES

`*.bdf` font files

3.8.5 johab2ucs2 SEE ALSO

`bdfimplode(1)`, `hex2bdf(1)`, `hex2sfd(1)`, `hexbraille(1)`, `hexdraw(1)`, `hexkinya(1)`, `hexmerge(1)`, `unibdf2hex(1)`, `unibmp2hex(1)`, `unibmpbump(1)`, `unicoverage(1)`, `unidup(1)`, `unifont(5)`, `unifont-viewer(1)`, `unifont1per(1)`, `unifontchojung(1)`, `unifontksx(1)`, `unifontpic(1)`, `unigenircles(1)`, `unigenwidth(1)`, `unihex2bmp(1)`, `unihex2png(1)`, `unihexfill(1)`, `unihexgen(1)`, `unihexrotate(1)`, `unipagecount(1)`, `unipng2hex(1)`

3.8.6 johab2ucs2 AUTHOR

`johab2ucs2` was written in 1998 by Jungshik Shin and given to Roman Czyborra. Paul Hardy made some modifications and bug fixes in 2008.

3.8.7 johab2ucs2 LICENSE

`johab2ucs2` is Copyright © 1998 Jungshik Shin and Roman Czyborra, © 2008 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.8.8 johab2ucs2 BUGS

No known bugs exist.

3.9 unibdf2hex

3.9.1 unibdf2hex NAME

`unibdf2hex` – Convert BDF font glyphs into Unifont `.hex` glyphs

3.9.2 unibdf2hex SYNOPSIS

`unibdf2hex` < *input-font.bdf* > *output-font.hex*

3.9.3 unibdf2hex DESCRIPTION

unibdf2hex reads a BDF font file, extracting selected code points and printing them on stdout in Unifont .hex format. This program was used to extract CJK ideographs from the 16x16 version of Wen Quan Yi's BDF font. Currently the program is hard-coded to only extract those code points that comprise the "wqy.hex" source font file used to build "unifont.hex" but this source code could easily be modified.

3.9.4 unibdf2hex FILES

*.hex GNU Unifont font files

3.9.5 unibdf2hex SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigenircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.9.6 unibdf2hex AUTHOR

unibdf2hex was written by Paul Hardy.

3.9.7 unibdf2hex LICENSE

unibdf2hex is Copyright © 2008 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.9.8 unibdf2hex BUGS

No known bugs exist.

3.10 unibmp2hex

3.10.1 unibmp2hex NAME

unibmp2hex – Bitmap graphics file to GNU Unifont .hex file converter

3.10.2 unibmp2hex SYNOPSIS

unibmp2hex [*-p*hexpage] [*-i*input_file.bmp] [*-o*output_file.hex] [*-w*]

3.10.3 unibmp2hex DESCRIPTION

unibmp2hex reads a bitmap produced by **unihex2bmp** before or after editing, and converts it back into a Unifont .hex format file. The graphics file contains a block of 256 Unicode code points arranged in a 16 by 16 grid. Each code point appears in a 32 by 32 pixel grid. Characters are 16 rows high, and 8, 16, or 31 (treated as 32) columns wide.

3.10.4 unibmp2hex OPTIONS

- p Specify that the code points will be assigned to the 256 block space *pagenum* in the .hex file. If not specified, **unibmp2hex** will determine the appropriate block by reading the row and column headers. Note that "page" is not a standard Unicode term. It refers to an output bitmap graphics page of 16 by 16 code points. If *pagenum* is greater than FF, the block resides above the Unicode Basic Multilingual Plane. In that event, the .hex file will contain eight digit hexadecimal code points rather than the Unifont standard of four hexadecimal code points.
- i Specify the input file. The default is STDIN.
- o Specify the output file. The default is STDOUT.
- w Force all output .hex glyphs to be 16 pixels wide rather than dual width (8 or 16 pixels).

3.10.5 unibmp2hex EXAMPLE

Sample usage:

```
unibmp2hex -imy_input_file.bmp -omy_output_file.hex
```

3.10.6 unibmp2hex FILES

*.bmp or *.wbmp graphics files

3.10.7 unibmp2hex SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifont-pic(1)**, **unigencircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.10.8 unibmp2hex AUTHOR

unibmp2hex was written by Paul Hardy.

3.10.9 unibmp2hex LICENSE

unibmp2hex is Copyright © 2007, 2008 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.10.10 unibmp2hex BUGS

No known real bugs exist, except that this software does not perform extensive error checking on its input files. If they're not in the format of the original bitmapped output from **unihex2bmp**, all bets are off.

If the output file is for a "page" containing space code points and the bitmap file squares for those code points are not empty, **unibmp2hex** preserves the graphics as they are drawn.

3.11 unibmpbump

3.11.1 unibmpbump NAME

unibmpbump – adjust a .bmp image for unibmp2hex processing

3.11.2 unibmpbump SYNOPSIS

unibmpbump [*-i*input-file.bmp] [*-o*output-file.bmp] [*-v*|*--verbose*] [*-V*|*--version*]

3.11.3 unibmpbump DESCRIPTION

unibmpbump reads a Microsoft Bitmap Graphics (".bmp") graphics image file and, if it appears to be in a known format, converts it for processing by **unibmp2hex**(1).

unibmpbump supports the following Device Independent Bitmap (DIB) header byte lengths for input image files:

- | | |
|-----|---|
| 12 | The BITMAPCOREHEADER format. This was the original Microsoft Windows header format. It has not been encountered, and was added only as a subset of the formats that appear below. |
| 40 | The BITMAPINFOHEADER format. This is the format that most graphics creation programs support, and is the header format that unibmp2hex expects. |
| 108 | The BITMAPV4HEADER format. This is the format that the Image Magick convert program creates when converting a PNG image to a BMP image using the " <i>--monochrome</i> " option. |
| 124 | The BITMAPV5HEADER format. This is the format that the Image Magick convert program creates when converting a PNG image to a BMP image without the " <i>--monochrome</i> " option; convert will encode the image as a "grayscale" image, but with only two colors: black and white. |

unibmpbump is able to read files created by **unihex2png** that were subsequently saved as BMP files, for example by the **convert**(1) program, which is part of the Image Magick package. Images created by **unihex2png**(1) are 544 rows high by 560 columns wide. Images created by **unihex2bmp**(1) are 544 rows high by 576 columns wide. Thus, if the input Bitmap Graphics file is 544 by 560 pixels, **unibmpbump** assumes that the file was originally a Portable Network Graphics (".png") file created by **unihex2png** and realigns the glyphs so they are positioned as **unibmp2hex** expects.

3.11.4 unibmpbump OPTIONS

- i** Specify an input Bitmaps Graphics (".bmp") file. If no input file is specified, input is taken from stdin. The input file must be either 544 rows by 560 columns (for a file created by **unihex2png** originally) or 544 rows by 576 columns (for a file created by **unihex2bmp** originally).
- o** Specify an output Bitmaps Graphics (".bmp") file. If no output file is specified, output is sent to stdout. The output file will be 544 rows high by 576 columns wide with a 40 byte Device Independent Bitmap (DIB) header, which is the format that **unibmp2hex** expects.

-v, --verbose

Verbose output. Print information about the input file on stderr.

-V, --version

Print the version of **unibmpbump** and exit.

3.11.5 unibmpbump FILES

Bitmap Graphics (".bmp") input and output files.

3.11.6 unibmpbump SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifont-pic(1)**, **unigencircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.11.7 unibmpbump AUTHOR

unibmpbump was written by Paul Hardy.

3.11.8 unibmpbump LICENSE

unibmpbump is Copyright © 2019 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.11.9 unibmpbump BUGS

No known bugs exist.

3.12 unicoverage

3.12.1 unicoverage NAME

unicoverage – Print coverage of each Unicode Script

3.12.2 unicoverage SYNOPSIS

unicoverage [*-iinput-file*] [*-ooutput-file*]

3.12.3 unicoverage DESCRIPTION

unicoverage reads a GNU Unifont .hex font and uses data in **coverage.dat** (which must reside in the current directory). The output is the percent coverage of each script listed in the coverage.dat file. The Unicode code points in the input .hex file must be in ascending order.

3.12.4 unicoverage OPTIONS

-i Specify the input file. The default is STDIN.

-o Specify the output file. The default is STDOUT.

3.12.5 unicoverage EXAMPLE

Sample usage:

```
unicoverage < unifont.hex >coverage.txt
```

3.12.6 unicoverage FILES

coverage.dat, *.hex GNU Unifont files.

3.12.7 unicoverage SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigenircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.12.8 unicoverage AUTHOR

unicoverage was written by Paul Hardy.

3.12.9 unicoverage LICENSE

unicoverage is Copyright © 2007, 2008 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.12.10 unicoverage BUGS

No known real bugs exist, except that this software does not perform extensive error checking on its input files.

3.13 unidup

3.13.1 unidup NAME

unidup – Scan through a sorted .hex file and report duplicate code points

3.13.2 unidup SYNOPSIS

```
unidup [input-font.hex]
```

3.13.3 unidup DESCRIPTION

unidup reads a sorted GNU Unifont .hex file (sorted with the Unix **sort** utility) and prints notification of any duplicate code points on stdout. The input file can be specified on the command line. If no file is specified, input will be read from STDIN until end of file.

3.13.4 unidup FILES

*.hex GNU Unifont font files

3.13.5 unidup SEE ALSO

`bdfimplode(1)`, `hex2bdf(1)`, `hex2sfd(1)`, `hexbraille(1)`, `hexdraw(1)`, `hexkinya(1)`, `hexmerge(1)`, `johab2ucs2(1)`, `unibdf2hex(1)`, `unibmp2hex(1)`, `unibmpbump(1)`, `unicoverage(1)`, `unifont(5)`, `unifont-viewer(1)`, `unifont1per(1)`, `unifontchojung(1)`, `unifontksx(1)`, `unifontpic(1)`, `unigenircles(1)`, `unigenwidth(1)`, `unihex2bmp(1)`, `unihex2png(1)`, `unihexfill(1)`, `unihexgen(1)`, `unihexrotate(1)`, `unipagecount(1)`, `unipng2hex(1)`

3.13.6 unidup AUTHOR

`unidup` was written by Paul Hardy.

3.13.7 unidup LICENSE

`unidup` is Copyright © 2007, 2013 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.13.8 unidup BUGS

No known bugs exist.

3.14 unifont-viewer

3.14.1 unifont-viewer NAME

`unifont-viewer` – View a `.hex` font file with a graphical user interface

3.14.2 unifont-viewer SYNOPSIS

`unifont-viewer` &

3.14.3 unifont-viewer DESCRIPTION

`unifont-viewer` reads a GNU Unifont `.hex` file and displays glyphs in blocks of 16 by 16, 256 glyphs per screen with a graphical user interface. The `.hex` file is selected by opening it with the **File > Open** menu item or by typing Control-O. After loading a file, a list of "pages" of 256 glyphs will appear in the left-hand column of the window. The first such page of glyphs in the file will appear in the main window.

`unifont-viewer` supports glyph heights of 16, 24, and 32 pixels. The height of a `.hex` font file is selected under the **File** menu. The default selection is **Glyph Height 16**.

Exit `unifont-viewer` by selecting **File > Exit** or by typing Control-X.

3.14.4 unifont-viewer FILES

`*.hex` GNU Unifont font files

3.14.5 unifont-viewer SEE ALSO

`bdfimplode(1)`, `hex2bdf(1)`, `hex2sfd(1)`, `hexbraille(1)`, `hexdraw(1)`, `hexkinya(1)`, `hexmerge(1)`, `johab2ucs2(1)`, `unibdf2hex(1)`, `unibmp2hex(1)`, `unibmpbump(1)`, `unicoverage(1)`, `unidup(1)`, `unifont(5)`, `unifont1per(1)`, `unifontchojung(1)`, `unifontksx(1)`,

unifontpic(1), **unigencircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.14.6 unifont-viewer AUTHOR

unifont-viewer was written by Andrew Miller.

3.14.7 unifont-viewer LICENSE

unifont-viewer is Copyright © 2014 Andrew Miller.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.14.8 unifont-viewer BUGS

No known bugs exist.

3.15 unifont1per

3.15.1 unifont1per NAME

unifont1per – Create BMP glyph files from GNU Unifont .hex file

3.15.2 unifont1per SYNOPSIS

unifont1per < *input_file.hex*

3.15.3 unifont1per DESCRIPTION

unifont1per reads a GNU Unifont .hex file and for each code point in the file, creates an output Bitmapped Graphics (".bmp") file in the current directory. The filename for each output file is "U+*codepoint*.bmp", where *codepoint* is the Unicode codepoint for the glyph. Each glyph entry in a Unifont .hex file is expected to be 16 rows tall, and can be 8, 16, 24, or 32 pixels wide. The glyph sizes in output files are determined on a glyph-by-glyph basis. This program can be of use in extracting individual glyphs to display in a document or on a web page.

WARNING! This program generates one output file per code point that appears in the input stream. If you feed this program a file with 1000 code points, it will generate 1000 files in your current directory.

3.15.4 unifont1per OPTIONS

None.

3.15.5 unifont1per FILES

*.hex GNU Unifont font files, read from standard input

3.15.6 unifont1per SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifontchojung(1)**, **unifontksx(1)**,

unifontpic(1), **unigencircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.15.7 unifont1per AUTHOR

unifont1per was written by Paul Hardy.

3.15.8 unifont1per LICENSE

unifont1per is Copyright © 2017 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.15.9 unifont1per BUGS

No known real bugs exist, except that this software does not perform extensive error checking on its input files. If they're not in the format of the original GNU Unifont .hex file, all bets are off. Lines can be terminated either with line feed, or carriage return plus line feed.

3.16 unifontchojung

3.16.1 unifontchojung NAME

unifontchojung – Extract Hangul syllables that have no final consonant

3.16.2 unifontchojung SYNOPSIS

unifontchojung < *input-font.hex* > *output-font.hex*

3.16.3 unifontchojung DESCRIPTION

unifontchojung reads a Unifont-format .hex font file from STDIN and writes a Unifont .hex file containing a subset to STDOUT. The subset that is output only contains syllables that contain an initial consonant (chojung) plus middle vowel (jungseong), with no final consonant (jongseong). This lets a font designer focus on this subset during font creation.

3.16.4 unifontchojung FILES

*.bdf font files

3.16.5 unifontchojung SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **uncoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigencircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.16.6 unifontchojung AUTHOR

unifontchojung was written by Paul Hardy.

3.16.7 unifontchojung LICENSE

unifontchojung is Copyright © 2012 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.16.8 unifontchojung BUGS

No known bugs exist.

3.17 unifontksx

3.17.1 unifontksx NAME

unifontksx – Extract Hangul syllables that comprise KS X 1001:1992

3.17.2 unifontksx SYNOPSIS

unifontksx < *input-font.hex* > *output-font.hex*

3.17.3 unifontksx DESCRIPTION

unifontksx reads a Unifont-format .hex font file from STDIN and writes a Unifont .hex file containing a subset to STDOUT. The subset that is output only contains the 2,350 syllables that comprise Korean Standard KS X 1001:1992. These are extracted from the Unicode Hangul Syllables block, U+AC00..U+D7A3. This lets a font designer focus on those syllables that are most common in modern Hangul usage during font development.

3.17.4 unifontksx FILES

*.bdf font files

3.17.5 unifontksx SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontpic(1)**, **unigencircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.17.6 unifontksx AUTHOR

unifontksx was written by Paul Hardy.

3.17.7 unifontksx LICENSE

unifontksx is Copyright © 2012 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.17.8 unifontksx BUGS

No known bugs exist.

3.18 unifontpic

3.18.1 unifontpic NAME

`unifontpic` – Convert GNU Unifont .hex input to a bitmap image of the whole font

3.18.2 unifontpic SYNOPSIS

```
unifontpic [-dnnn] [-l] [-t] [-Pplane] < input-font.hex > output-font.bmp
```

3.18.3 unifontpic DESCRIPTION

unifontpic reads a GNU Unifont .hex file from STDIN and writes a two dimensional rendering for each glyph to STDOUT. The output displays an entire Unicode plane of 65,536 glyphs as one large graphic image, showing a grid of 256 glyphs by 256 glyphs as the default, or (at your option) a long version of 16 glyphs across by 4,096 glyphs down.

Input can be one or more files in Unifont .hex format. They don't have to be sorted, as **unifontpic** will populate the entire glyph array of 65,536 code points before writing its output. The input glyph code points should all be unique, as feeding in duplicate code points will produce unpredictable results. Use **unidup (1)** on a sorted input of .hex files to guarantee no code point duplication.

3.18.4 unifontpic OPTIONS

- d** Specify a Dots per Inch (DPI) resolution of *nnn*. For example, specifying `-d120` will encode the bitmap graphics file output as having a resolution of 120 DPI.
- l** Produce a long chart, 16 glyphs wide by 4,096 glyphs tall. The default is a wide chart, 256 glyphs wide by 256 glyphs tall.
- t** Use tiny numbers for the row and column code point labels. Tiny numbers are on a 4 by 5 pixel grid. Only tiny code point labels appear on the long chart variant; this option only has effect for wide charts (the default, of 256 by 256 glyphs). If this option is not specified for the default 256-by-256 grid, row and column code point labels are taken from Unifont's glyphs for '0' to '9' and 'A' to 'F'.
- P** Print a chart for Unicode plane number *plane*. The default is Plane 0, the Unicode Basic Multilingual Plane (BMP). The range of Unicode plane range is 0 through 17, inclusive. The plane number is printed on the chart title line.

3.18.5 unifontpic EXAMPLES

Sample usage:

```
cat *.hex | unifontpic -d120 > unifontpic.bmp
```

To generate a bitmap that shows combining circles, from the **font/** subdirectory:

```
sort plane00/*.hex | unigencircles ttfsrc/combining.txt | unifontpic -d120
>unifontpic.bmp
```

3.18.6 unifontpic FILES

*.hex GNU Unifont font files

3.18.7 unifontpic SEE ALSO

`bdfimplode(1)`, `hex2bdf(1)`, `hex2sfd(1)`, `hexbraille(1)`, `hexdraw(1)`, `hexkinya(1)`, `hexmerge(1)`, `johab2ucs2(1)`, `unibdf2hex(1)`, `unibmp2hex(1)`, `unibmpbump(1)`, `unicoverage(1)`, `unidup(1)`, `unifont(5)`, `unifont-viewer(1)`, `unifont1per(1)`, `unifontchojung(1)`, `unifontksx(1)`, `unigencircles(1)`, `unigenwidth(1)`, `unihex2bmp(1)`, `unihex2png(1)`, `unihexfill(1)`, `unihexgen(1)`, `unihexrotate(1)`, `unipagecount(1)`, `unipng2hex(1)`

3.18.8 unifontpic AUTHOR

`unifontpic` was written by Paul Hardy.

3.18.9 unifontpic LICENSE

`unifontpic` is Copyright © 2013 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.18.10 unifontpic BUGS

No known bugs exist.

3.19 unigencircles

3.19.1 unigencircles NAME

`unigencircles` – Add dashed combining circles to a `unifont.hex` file

3.19.2 unigencircles SYNOPSIS

`unigencircles combining.txt nonprinting.hex < unifont.hex > unifont-circles.hex`

3.19.3 unigencircles DESCRIPTION

`unigencircles` reads a `unifont.hex` file from STDIN, adds dashed combining circles to the hex strings for code points listed in "combining.txt" but not listed in "nonprinting.hex", and writes the revised set of glyphs in `unifont.hex` format to STDOUT. The resulting combining character glyphs show the dashed combining circles that appear in The Unicode Standard code charts.

For each code point listed in the "combining.txt" file but not listed in the "nonprinting.hex" file, `unigencircles` will superimpose a single-width dashed circle in glyphs that are single-width (i.e., their hex glyph strings are 32 characters long) and will superimpose a double-width dashed circle in glyphs that are double-width (i.e., their hex glyph strings are 64 characters long).

3.19.4 unigencircles EXAMPLE

```
unigencircles combining.txt nonprinting.hex < unifont.hex > unifont-circles.hex
```

3.19.5 unigencircles FILES

*.hex files for Unifont glyph data

`font/ttfsrc/combining.txt` for combining code points

`font/plane00/nonprinting.hex` for non-printing code points

3.19.6 unigencircles SEE ALSO

`bdfimplode(1)`, `hex2bdf(1)`, `hex2sfd(1)`, `hexbraille(1)`, `hexdraw(1)`, `hexkinya(1)`, `hexmerge(1)`, `johab2ucs2(1)`, `unibdf2hex(1)`, `unibmp2hex(1)`, `unibmpbump(1)`, `unicoverage(1)`, `unidup(1)`, `unifont(5)`, `unifont-viewer(1)`, `unifont1per(1)`, `unifontchojung(1)`, `unifontksx(1)`, `unifontpic(1)`, `unigenwidth(1)`, `unihex2bmp(1)`, `unihex2png(1)`, `unihexfill(1)`, `unihexgen(1)`, `unihexrotate(1)`, `unipagecount(1)`, `unipng2hex(1)`

3.19.7 unigencircles AUTHOR

`unigencircles` was written by Paul Hardy.

3.19.8 unigencircles LICENSE

`unigencircles` is Copyright © 2013 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.19.9 unigencircles BUGS

No known real bugs exist, except that this software does not perform extensive error checking on its input files.

3.20 unigenwidth

3.20.1 unigenwidth NAME

`unigenwidth` – Generate C code for POSIX `wcwidth` and `wcswidth` functions

3.20.2 unigenwidth SYNOPSIS

`unigenwidth` *unifont.hex combining.txt* > *wccode.c*

3.20.3 unigenwidth DESCRIPTION

`unigenwidth` reads a collection of glyphs in Unifont’s `.hex` format, then reads a list of combining characters as a hexadecimal list. From these two files, it produces C code to implement the POSIX `wcwidth(3)` and `wcswidth(3)` functions. The format of these definitions is based upon POSIX 1003.1-2008 System Interfaces, pages 2251 and 2241, respectively.

3.20.4 unigenwidth EXAMPLE

Sample usage:

```
unigenwidth unifont.hex combining.txt > wccode.c
```

3.20.5 unigenwidth FILES

`*.hex` files for Unifont glyph data; `combining.txt` for combining code points.

3.20.6 unigenwidth SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigencircles(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.20.7 unigenwidth AUTHOR

unigenwidth was written by Paul Hardy.

3.20.8 unigenwidth LICENSE

unigenwidth is Copyright © 2013 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.20.9 unigenwidth BUGS

No known real bugs exist, except that this software does not perform extensive error checking on its input files.

3.21 unihex2bmp

3.21.1 unihex2bmp NAME

unihex2bmp – GNU Unifont .hex file to bitmap graphics file converter

3.21.2 unihex2bmp SYNOPSIS

```
unihex2bmp [-hexpage] [-input_file.hex] [-output_file.bmp] [-f] [-w]
```

3.21.3 unihex2bmp DESCRIPTION

unihex2bmp reads a GNU Unifont .hex file Unicode page of 256 code points and converts the page into a Microsoft Windows Bitmap (.bmp) or Wireless Bitmap (.wbmp) file. The bitmap file displays the glyphs of a Unicode block of 256 code points in a 32 by 32 pixel grid. The glyphs themselves must be 16 rows high, and 8, 16, 24, or 31 (encoded as 32) columns wide. The default page is 0; that is, the range U+0000 through U+00FF.

The bitmap can be printed. It can also be edited with a bitmap editor. An edited bitmap can then be re-converted into a GNU Unifont .hex file with the **unibmp2hex** command.

3.21.4 unihex2bmp OPTIONS

- p Extract page *hexpage* from the .hex file. The default is Page 0 (Unicode range U+0000 through U+00FF). Note that "page" is not a standard Unicode term. It refers to an output bitmap graphics page of 16 by 16 code points.
- i Specify the input file. The default is STDIN.
- o Specify the output file. The default is STDOUT.

- f** "Flip" (transpose) the grid, swapping rows and columns from the Unicode standard orientation.
- w** Produce a Wireless Bitmap format file instead of a Microsoft Windows Bitmap file.

3.21.5 unihex2bmp EXAMPLE

Sample usage:

```
unihex2bmp -imy_input_file.hex -omy_output_file.bmp
```

3.21.6 unihex2bmp FILES

*.hex GNU Unifont font files

3.21.7 unihex2bmp SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigencircles(1)**, **unigenwidth(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.21.8 unihex2bmp AUTHOR

unihex2bmp was written by Paul Hardy.

3.21.9 unihex2bmp LICENSE

unihex2bmp is Copyright © 2007 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.21.10 unihex2bmp BUGS

No known real bugs exist, except that this software does not perform extensive error checking on its input files. If they're not in the format of the original GNU Unifont .hex file, all bets are off. Lines can be terminated either with line feed, or carriage return plus line feed.

3.22 unihex2png

3.22.1 unihex2png NAME

unihex2png – GNU Unifont .hex file to Portable Network Graphics converter

3.22.2 unihex2png SYNOPSIS

```
unihex2png [-i input_file.hex] [-o output_file.png] [-p pagenum] [-r rows]
```

3.22.3 unihex2png DESCRIPTION

unihex2png reads a page of 256 Unicode code points from a GNU Unifont .hex file and converts the page into a Portable Network Graphics (PNG) file. The graphics file displays

the glyphs of a Unicode block of 256 code points in a 32 by 32 pixel grid, or in a 40 by 40 pixel grid if "`-r 32`" is specified. The glyphs themselves can be either 16, 24, or 32 pixels tall depending on the "`-r`" parameter. They can be 8, 16, 24, or 32 pixels wide (widths of 32 are only supported if "`-r 32`" is specified). The default page is 0; that is, the range U+0000 through U+00FF, inclusive.

The PNG file can be printed. It can also be edited with a graphics editor. An edited PNG file can then be re-converted into a GNU Unifont `.hex` file with the `unipng2hex` command.

3.22.4 unihex2png OPTIONS

- `-i` Specify the input file. If not omitted, a Unifont `.hex` file is read from STDIN.
- `-o` Specify the output file.
- `-p` Extract page *pagenum* from the `.hex` file. The default is Page 0 (Unicode range U+0000 through U+00FF). Note that "page" is not a standard Unicode term. It refers to an output bitmap graphics page of 16 by 16 code points.
- `-r` Specify the *rows* of pixels in the output glyphs. Valid values are 16, 24, and 32. The default is 16 pixel rows tall.
- `-h` Print a help message of options and exit.

3.22.5 unihex2png EXAMPLE

Sample usage:

```
unihex2png -i my_input_file.hex -o my_output_file.png
```

3.22.6 unihex2png FILES

*.hex GNU Unifont font files

3.22.7 unihex2png SEE ALSO

`bdfimplode(1)`, `hex2bdf(1)`, `hex2sfd(1)`, `hexbraille(1)`, `hexdraw(1)`, `hexkinya(1)`, `hexmerge(1)`, `johab2ucs2(1)`, `unibdf2hex(1)`, `unibmp2hex(1)`, `unibmpbump(1)`, `unicoverage(1)`, `unidup(1)`, `unifont(5)`, `unifont-viewer(1)`, `unifont1per(1)`, `unifontchojung(1)`, `unifontksx(1)`, `unifontpic(1)`, `unigencircles(1)`, `unigenwidth(1)`, `unihex2bmp(1)`, `unihexfill(1)`, `unihexgen(1)`, `unihexrotate(1)`, `unipagecount(1)`, `unipng2hex(1)`

3.22.8 unihex2png AUTHOR

`unihex2png` was written by Andrew Miller, starting by converting Paul Hardy's `unihex2bmp` C program to Perl.

3.22.9 unihex2png LICENSE

`unihex2png` is Copyright © 2007 Paul Hardy, © 2013 Andrew Miller.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.22.10 unihex2png BUGS

No known real bugs exist, but the optional pixel rows parameter is not yet supported by all other Unifont utilities. Use of glyphs taller than the default of 16 pixels is considered experimental. Currently **unihex2png**, **unipng2hex**, **hexdraw**, and **hex2bdf** tentatively support glyphs that are 16, 24, and 32 pixels tall.

Also, there is no extensive error checking on input files. If they're not in the format of the original GNU Unifont .hex file, all bets are off. Lines can be terminated either with line feed, or carriage return plus line feed.

3.23 unihexfill

3.23.1 unihexfill NAME

unihexfill – Generate range of Unifont 4- or 6-digit hexadecimal glyphs

3.23.2 unihexfill SYNOPSIS

```
unihexfill < unassigned-ranges.txt > filler-glyphs.hex
```

3.23.3 unihexfill DESCRIPTION

unihexfill is a shell script that reads a list of code point ranges from STDIN and produces filler glyphs of 4- or 6-digit code points on STDOUT. The format of the input file is a combination of comment lines, single code points on a line, and start/stop pairs of code points on a line separated by a space. Comment lines start with a semicolon (;) by convention. Start and stop code points are strings of hexadecimal digits, by convention either four or six digits. **unihexfill** invokes **unihexgen** for each non-comment line in its input file. If a codepoint is less than or equal to "FFFF" (i.e., 0xFFFF), a four-digit hexadecimal number is encoded within the corresponding Unifont glyph as two digits on each of two rows. Otherwise, a six-digit hexadecimal number is encoded as three digits on each of two rows.

3.23.4 unihexfill OPTIONS

There are no options.

3.23.5 unihexfill FILES

*.txt as input; *.hex as output.

3.23.6 unihexfill EXAMPLE

In the Unifont source package, the file font/plane01/Makefile generates Unicode Plane 1 hexadecimal filler glyphs of unassigned code points within assigned scripts with this single-line command:

```
../bin/unihexfill < unassigned-ranges.txt > unassigned.hex
```

3.23.7 unihexfill SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**,

unifontksx(1), unifontpic(1), unigencircles(1), unigenwidth(1), unihex2bmp(1), unihex2png(1), unihexgen(1), unihexrotate(1), unipagecount(1), unipng2hex(1)

3.23.8 unihexfill AUTHOR

unihexfill was written by Paul Hardy.

3.23.9 unihexfill LICENSE

unihexfill is Copyright © 2014 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.23.10 unihexfill BUGS

No known real bugs exist, except that this software does not perform extensive error checking on its input file. Any line that appears to begin with a hexadecimal digit is fed to **unihexgen**.

3.24 unihexgen

3.24.1 unihexgen NAME

unihexgen – Generate Unifont 4- or 6-digit hexadecimal glyphs

3.24.2 unihexgen SYNOPSIS

unihexgen *startpoint endpoint*

3.24.3 unihexgen DESCRIPTION

unihexgen produces unifont.hex entries in the Unicode code point range *startpoint* to *endpoint* (specified as the two command-line arguments). Output is to STDOUT. If a codepoint is less than or equal to "FFFF" (i.e., 0xFFFF), a four-digit hexadecimal number is encoded within the corresponding Unifont glyph as two digits on each of two rows. Otherwise, a six-digit hexadecimal number is encoded as three digits on each of two rows.

3.24.4 unihexgen OPTIONS

There are no options.

3.24.5 unihexgen FILES

*.hex as output.

3.24.6 unihexgen EXAMPLE

To generate the Private Use Area glyphs in the Unicode range U+E000..U+F8FF, invoke **unihexgen** with these arguments:

```
unihexgen e000 f8ff
```

3.24.7 unihexgen SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigencircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexrotate(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.24.8 unihexgen AUTHOR

unihexgen was written by Paul Hardy.

3.24.9 unihexgen LICENSE

unihexgen is Copyright © 2013 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.24.10 unihexgen BUGS

No known real bugs exist, except that this software does not perform extensive error checking on its command-line arguments. If they're not in the format of the original bitmapped output from **unihexgen**, all bets are off.

3.25 unihexrotate

3.25.1 unihexrotate NAME

unihexrotate – rotate Unifont hex glyphs in quarter turn increments

3.25.2 unihexrotate SYNOPSIS

unihexrotate [*-n quarter-turns*] [*input-font.hex*] > *output-font.hex*

3.25.3 unihexrotate DESCRIPTION

unihexrotate reads a GNU Unifont .hex format file named on the command line, or from stdin if no filename is given. If a number of quarter turns is specified, it rotates each glyph clockwise by that number of quarter turns, or counterclockwise if the number is negative. The resulting modified .hex file is written to stdout. The format of a .hex file is described in the **unifont(5)** man page.

If the number of quarter turns is not specified, **unihexrotate** will rotate each glyph by a default value of one quarter turn (i.e., 90 degrees) clockwise.

unihexrotate only supports Unifont .hex files with glyphs that are 8 columns and 16 columns wide. If an 8-column glyph is rotated, it is first centered within a 16-column glyph so the rotation will be performed on a 16-by-16 pixel glyph. One additional use of this program is that a glyph can be converted from 8~columns wide to 16~columns wide by specifying a rotation of 0~quarter turns.

3.25.4 unihexrotate OPTIONS

- n** Specify an integer number of quarter turn clockwise rotations to perform, typically as "`-n\~0`" through "`-n\~3`" (alternatively as "`-n=0`" through "`-n=3`") for rotations of 0, 90, 180, or 270 degrees, respectively. Negative values will perform counterclockwise rotations by the specified number of quarter turns.

3.25.5 unihexrotate EXAMPLES

This example extracts the Mongolian glyphs in the "unifont-base.hex" file (located in the "font/plane00" directory) and pipes them to **unihexrotate** to rotate by the default amount of one quarter turn clockwise (i.e., by 90 degrees). The basic Mongolian glyphs are in the Unicode range U+1800 through U+18AF. The original glyphs in "unifont-base.hex" are drawn for horizontal rendering (as per the Unicode Standard). The output rotated glyphs are suitable for rendering Mongolian in its traditional vertical form. Because no filename is specified to **unihexrotate** in this example, its input is taken from stdin.

```
grep "^18[0-A]" unifont-base.hex | unihexrotate > vertical.hex
```

The next example reverses the rotation performed above, by one quarter turn counterclockwise. In this example, the input filename "vertical.hex" is specified.

```
unihexrotate -n -1 vertical.hex > horizontal.hex
```

3.25.6 unihexrotate FILES

Unifont .hex format input and output files.

3.25.7 unihexrotate SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigencircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unipagecount(1)**, **unipng2hex(1)**

3.25.8 unihexrotate AUTHOR

unihexrotate was written by David Corbett.

3.25.9 unihexrotate LICENSE

unihexrotate is Copyright © 2019 David Corbett.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.25.10 unihexrotate BUGS

No known bugs exist.

3.26 unipagecount

3.26.1 unipagecount NAME

unipagecount – Count the assigned code points in a GNU Unifont .hex file

3.26.2 unipagecount SYNOPSIS

unipagecount [-P*plane*] [-ppagenum] [-h|-l]

3.26.3 unipagecount DESCRIPTION

unipagecount reads a GNU Unifont .hex file from STDIN and prints a 16 by 16 grid of the number of defined code points in each 256 character block within a Unicode plane to STDOUT. Code points proceed from left to right, then top to bottom. In all planes, code points U+*FFFE and U+*FFFF are not expected in the input hex file; they are reserved and always counted as being present in a plane.

3.26.4 unipagecount OPTIONS

- P Select a Unicode plane, from 0 through 16, inclusive. If not specified, **unipagecount** defaults to Plane 0 (the Basic Multilingual Plane).
- p Just print information on one 256 code point "page" rather than the entire Basic Multilingual Plane. This prints a 16 by 16 table with an asterisk in every code point that has an assigned glyph.
- h Print an HTML table with color-coded cell background colors instead of a plain text table.
- l [The letter "l"]: Print hyperlinks to font bitmaps in the HTML table. To create the bitmaps themselves, use the **unihex2bmp** program. The bitmaps are assumed to be in the directory "bmp/".

3.26.5 unipagecount FILES

*.hex GNU Unifont font files

3.26.6 unipagecount SEE ALSO

bdfimplode(1), **hex2bdf(1)**, **hex2sfd(1)**, **hexbraille(1)**, **hexdraw(1)**, **hexkinya(1)**, **hexmerge(1)**, **johab2ucs2(1)**, **unibdf2hex(1)**, **unibmp2hex(1)**, **unibmpbump(1)**, **unicoverage(1)**, **unidup(1)**, **unifont(5)**, **unifont-viewer(1)**, **unifont1per(1)**, **unifontchojung(1)**, **unifontksx(1)**, **unifontpic(1)**, **unigencircles(1)**, **unigenwidth(1)**, **unihex2bmp(1)**, **unihex2png(1)**, **unihexfill(1)**, **unihexgen(1)**, **unihexrotate(1)**, **unipng2hex(1)**

3.26.7 unipagecount AUTHOR

unipagecount was written by Paul Hardy.

3.26.8 unipagecount LICENSE

unipagecount is Copyright © 2007, 2014 Paul Hardy.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.26.9 unipagecount BUGS

No known real bugs exist, except that this software does not perform extensive error checking on its input files. If they're not in the format of the original GNU Unifont .hex file, all bets are off.

3.27 unipng2hex

3.27.1 unipng2hex NAME

`unipng2hex` – Portable Network Graphics to GNU Unifont .hex file converter

3.27.2 unipng2hex SYNOPSIS

```
unipng2hex -i input_file.png [-o output_file.hex] [-w width]
```

3.27.3 unipng2hex DESCRIPTION

`unipng2hex` reads a PNG file produced by `unihex2png` before or after editing, and converts it back into a Unifont .hex format file. The PNG file contains a block of 256 Unicode code points arranged in a 16 by 16 grid. Each code point appears in a 32 by 32 or a 40 by 40 pixel grid. Characters are either 16, 24 or 32 pixel rows high, depending on the "-r" parameter specified by `unihex2png`. They can be 8, 16, 24, or 32 pixel columns wide (widths of 32 are only supported for 32 pixel row tall characters).

3.27.4 unipng2hex OPTIONS

- i Specify the input file.
- o Specify the output file. If omitted, a file in the Unifont .hex format is written to STDOUT.
- w Specify the minimum width of the output glyphs. Valid values are 16, 24, and 32. The default is no minimum width.
- h Print a help message of options and exit.

3.27.5 unipng2hex EXAMPLE

Sample usage:

```
unipng2hex -i my_input_file.png -o my_output_file.hex
```

3.27.6 unipng2hex FILES

*.png graphics files

3.27.7 unipng2hex SEE ALSO

`bdfimplode(1)`, `hex2bdf(1)`, `hex2sfd(1)`, `hexbraille(1)`, `hexdraw(1)`, `hexkinya(1)`, `hexmerge(1)`, `johab2ucs2(1)`, `unibdf2hex(1)`, `unibmp2hex(1)`, `unibmpbump(1)`, `unicoverage(1)`, `unidup(1)`, `unifont(5)`, `unifont-viewer(1)`, `unifont1per(1)`, `unifontchojung(1)`, `unifontksx(1)`, `unifontpic(1)`, `unigencircles(1)`, `unigenwidth(1)`, `unihex2bmp(1)`, `unihex2png(1)`, `unihexfill(1)`, `unihexgen(1)`, `unihexrotate(1)`, `unipagecount(1)`

3.27.8 unipng2hex AUTHOR

`unipng2hex` was written by Andrew Miller, starting by converting Paul Hardy's `unibmp2hex` C program to Perl.

3.27.9 unipng2hex LICENSE

unipng2hex is Copyright © 2007, 2008 Paul Hardy, © 2013 Andrew Miller.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

3.27.10 unipng2hex BUGS

No known real bugs exist, but the optional pixel rows parameter is not yet supported by all other Unifont utilities. Use of glyphs taller than the default of 16 pixels is considered experimental. Currently **unihex2png**, **unipng2hex**, **hexdraw**, and **hex2bdf** tentatively support glyphs that are 16, 24, and 32 pixels tall.

Also, this software does not perform extensive error checking on its input files. If they're not in the format of the original PNG output from **unihex2png**, all bets are off.

If the output file is for a "page" containing space code points and the PNG file squares for those code points are not empty, **unipng2hex** preserves the graphics as they are drawn.

unipng2hex is designed to work with black and white pixels; do not use other colors.